

PRODUCT FEATURES & BENEFITS

Asian Paints Exterior Wall Putty is a specially designed product based on White Cement, Re dispersible polymer, and functional additives for application on exterior rough plasters to give a smooth finish

Asian Paints Exterior Wall Putty provides a smooth and uniform finish to rough plasters

The product has the following features/ Benefits

- * Good workability
- * Does not require curing with water
- * Good water resistance
- * Good tensile adhesion strength, Compressive strength and also flexural strength
- * Controlled water vapor permeability
- * Excellent abrasion resistance
- * Resists the growth of algae and fungi on wall
- * Good inter-coat adhesion to Emulsion Paints

We do not add Lead, Mercury, Arsenic or Chromium and other raw materials containing heavy metals in the manufacturing process.

Asian Paints Exterior Wall Putty is an Exterior Putty that can be applied on all types cement plasters, exterior ceilings, asbestos sheets, concrete etc.



SURFACE



EXTERIOR

AVAILABLE PACKS



Shelf life: 9 months from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

COLOURS AVAILABLE



White

FINISH



Refer to sheen levels in technical details

COVERAGE

On normal masonry surface by brushing



**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.

HOW TO APPLY

Cleaning: Ensure that the surface to be painted is free from any loose paint, dust or grease. Any previous growth of fungus, algae or moss needs to be removed.

Filling: Minor surface imperfections such as holes, dents and cracks are to be filled using mixture of white cement & fine sand (in the ratio of 1:3)

Freshly Plastered surface must be allowed to cure completely. Wet the surface before application of Exterior putty. Apply as follows.

PRE PAINTING STEPS



PLASTER New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.



FILLING FOR CRACKS For filling cracks upto 3mm use Asian Paints SmartCare Crack Seal.



CLEANING Surface should be free from any loose paint, dust or grease. Growths of fungus, algae or moss should be removed by wire brushing and water. In case of areas having excessive dampness use Asian Paints SmartCare Damp Proof to limit further dampness. When the underlying surface exhibits chalkiness, in spite of thorough surface cleaning, use Asian Paints SmartCare Exterior Sealer.



FILLING FOR HOLES & DENTS

In case of dents and holes use Asian Paints Wall Putty or white cement and fine sand in the ratio 1:3

For exterior surfaces or substrates that are subjected to continuous seepage or dampness, kindly use Asian Paints SmartCare DampProof, before the top coat application.

PAINT APPLICATION PROCESS

Product	Product Code	Thinner	Dilution % (by vol)	Application Viscosity (sec)	Re coating* Period (hrs)
Asian Paints Exterior Wall Filler 1st coat by Brush	AP 35	Water	50-60	60-70 KU	4 hrs
Asian Paints Exterior Wall Putty 1st coat	AP 41	N/A	40%	N/A	6-8 hrs
Asian Paints Exterior Wall Putty 2nd coat, sand down with 180 and 220 Emery paper, wipe Clean	AP 41	N/A	40%	N/A	12-14hrs
Asian Paints Exterior Wall Filler Brush or Roller	AP 35	Water	50-60	60-70 KU	12-14hrs

*Re coat period is quoted for 25°C and 50% Relative Humidity. These may vary under different conditions

ADDITIONAL INFORMATION

TECHNICAL DATA

- | | |
|---------------------------------|--|
| a) Pot Life of thinned material | : 2.5-3.5 Hours (Temp. $30^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and RH $65\% \pm 5\%$) |
| b) Dry to Re coat | : 6-8 hrs (Temp. $30^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and RH $65\% \pm 5\%$) |
| c) Coverage | : 2-2.5 Sq. mtr/kg (5-15 sq ft/kg) |
| d) Shelf-life | : 9 months from the date of manufacture in tightly sealed plastic bags kept in dry and cool place. |

** Actual coverage may vary from the quoted coverage due to factors such as methods and condition of application and surface roughness

PRECAUTIONS

- Kindly refer to the MSDS for Asian Paints Exterior Putty which gives detailed information of safety measures while handling the paint
- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application
- Do not use Asian Paints Universal Stainers or any other colourants.
- Mix well before use.
- Do not over thin

POST APPLICATION INSTRUCTIONS

Ensure surface is cleaned & dry before application of primer

SAFETY FEATURES

- Non-Flammable
- Kindly refer to the MSDS for Asian Paints Exterior Wall Putty which gives detailed information on safety measures while handling the paint.
- Store the bag tightly closed, in a cool, dry place.
- Keep out of reach of children and away from food, drink.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour or dust. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the putty or in water courses.
- In the event of spills, contain spillage using sand or earth.
- Safety Data Sheet available for professional user on request.
- No added Lead, Mercury or Chromium compounds.